

6 way include 125A switch-disconnector

- Type B 3P+N Distribution board
- 6 ways
- Integrated with 4P 125A switch-disconnector as incomer
- Supplied with dual earth and neutral terminals
- Accepts SP, DP and TP MCBs
- Accepts single module or three module width RCBOs
- Accepts single module width AFDDs
- Complies with BS EN 61439-3



General information

Mounting method	Surface mounted
Pole configuration	TPN
Number of ways (Type B Board)	6
Rated current of incomer	125
Incomer device	Switch-disconnector 4P 125A
Barcode (EAN-13)	5060690139300

Technical information

Standard	BS EN 61439-3
Number of phases	Three phase
Rated operational voltage (U_e)	[V] 400
Type of current	AC
Frequency (f)	[Hz] 50
Location type	Indoor
Degree of protection (IP)	IP30
Enclosure material	Steel
Surface finish	Powder coating
Colour	Grey
RAL colour number	7035
Busbar type	Fixed solid copper
Cable entry facility	Top & bottom plates removable for ease of drill or through knock-out at side
Protection device type	Miniature circuit breaker (MCB), SP, DP or TP, up to 63A (10kA) and 100A (6kA), B, C and D curve Residual current circuit breaker with overcurrent protection (RCBO), up to 50A (SP) or 63A (TP) Arc fault detection device (AFDD), up to 50A
Pollution degree	3


Danson Electrical UK Limited.

Package information

Package level 1		
Type		Box
Number of units in package level 1	[pcs]	1
Weight	[kg]	14.48
Length	[cm]	60.5
Width	[cm]	46
Height	[cm]	14.5
Package level 2		
Type		Pallet
Number of units in package level 2	[pcs]	24
Weight	[kg]	362.5
Length	[cm]	120
Width	[cm]	100
Height	[cm]	125

Dimensions

Width [mm]	Height [mm]	Depth [mm]	X hole [mm]	Y hole [mm]	Weight [kg]
450	591	120	360	466	13.48



Certificate

